

AGROLOX

RADIAL TRACTOR TYRES

60 SERIES	Product Code	Tyre Size	TT/TL	Inflated Unloaded Dimension		Load Index	Speed Symbol	Load & Pressure		Dynamic Rolling Circumference	Static Loaded Radius
				Section Width	Overall Diameter			Tyre Load Capacity	Tyre Pressure At Max. Load		
				mm	mm			kg	psi		
	UR6032900302OZK	900/60 R32	TL	905	1870	182/185	D/A8	8500/9250	58	5543	829
65 SERIES	UR6518320302OZK	320/65 R18	TL	319	873	109/109	A8/B	1030/1030	23	2612	395
	UR6520440302OZK	440/65 R20	TL	441	1080	138/141	D/A8	2360/2580	35	3213	483
	UR6524440302OZK	440/65 R24	TL	441	1182	135/138	D/A8	2180/2385	35	3534	534
	UR6528440302OZK	440/65 R28	TL	445	1285	131/134	D/A8	1950/2120	35	3857	585
	UR6524480302OZK	480/65 R24	TL	479	1234	133/136	D/A8	2060/2255	23	3681	555
	UR6528480302OZK	480/65 R28	TL	479	1335	136/139	D/A8	2240/2455	23	3998	605
	UR6528540302OZK	540/65 R28	TL	550	1413	149/152	D/A8	3250/3560	35	4219	636
	UR6530540302OZK	540/65 R30	TL	550	1470	150/153	D/A8	3350/3650	35	4396	664
	UR6534540302OZK	540/65 R34	TL	550	1575	152/155	D/A8	3550/3875	35	4725	716
	UR6538540302OZK	540/65 R38	TL	550	1675	153/156	D/A8	3650/4000	35	5039	767
	UR6528600302OZK	600/65 R28	TL	601	1491	154/157	D/A8	3750/4105	35	4407	657
	UR6538600302OZK	600/65 R38	TL	601	1745	154/157	D/A8	3750/4105	35	5237	795
UR6538650302OZK	650/65 R38	TL	650	1820	163/166	D/A8	4875/5300	35	5449	825	
UR6542650302OZK	650/65 R42	TL	650	1913	165/168	D/A8	5150/5600	35	5744	872	
70 SERIES	UR7028320302OZK	320/70 R28	TL	319	1189	119/119	A8/B	1360/1360	23	3585	547
	UR7024380302OZK	380/70 R24	TL	380	1190	125/128	D/A8	1650/1800	23	3556	537
	UR7028380302OZK	380/70 R28	TL	380	1293	127/130	D/A8	1750/1910	23	3879	588
	UR7024420302OZK	420/70 R24	TL	418	1248	130/133	D/A8	1900/2080	23	3720	560
	UR7028420302OZK	420/70 R28	TL	418	1351	133/136	D/A8	2060/2250	23	4043	612
	UR7028480302OZK	480/70 R28	TL	480	1425	140/143	D/A8	2500/2730	23	4253	641
	UR7034480302OZK	480/70 R34	TL	479	1580	143/146	D/A8	2725/2980	23	4739	718
	UR7038480302OZK	480/70 R38	TL	480	1685	145/148	D/A8	2900/3170	23	5067	771
	UR7034520302OZK	520/70 R34	TL	516	1640	148/151	D/A8	3150/3440	23	4908	742
	UR7038520302OZK	520/70 R38	TL	516	1749	150	D	3350	23	5223	793
	UR7038580302OZK	580/70 R38	TL	577	1827	155	D	3875	23	5441	823
	UR7046620302OZK	620/70 R46	TL	625	2036	162/165	D/A8	4750/5200	23	6124	931
	UR7038710302OZK	710/70 R38	TL	716	1959	171/174	D/A8	6150/6730	35	5842	880
UR7042710302OZK	710/70 R42	TL	716	2061	173/176	D/A8	6500/7120	35	6162	931	
85 SERIES	UR8528420302OZK	420/85 R28	TL	418	1425	139/139	A8/B	2430/2430	23	4252	641
	UR8538520302OZK	520/85 R38	TL	516	1849	155/155	A8/B	3880/3880	23	5531	836
	UR8538520302OZR	520/85 R38 REINFORCED FOR HARVESTER	TL	516	1849	169/169	A8/B	5800/5800	52	5531	836
	UR8542520302OZK	520/85 R42	TL	516	1951	157/157	A8/B	4130/4130	23	5851	887
90 SERIES	UR9030420302OZK	420/90 R30	TL	418	1518	147/147	A8/B	3080/3080	35	4531	683